

Safety Data Sheet

according to UK REACH Regulation

Flux-Remover

Revision date: 16.05.2024

Product code: 107

Page 2 of 9

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P211 Do not spray on an open flame or other ignition source.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P273 Avoid release to the environment.
 P271 Use only outdoors or in a well-ventilated area.
 P251 Do not pierce or burn, even after use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Additional advice on labelling

The components in this formulation do not meet the criteria for classification as PBT or vPvB. The components in this formulation do not meet the criteria for classification as PBT or vPvB.

2.3. Other hazards

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C9, aromatics			20-40%
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			30-35%
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
123-86-4	n-butyl acetate			15-20%
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
109-87-5	Dimethoxymethane			5-10%
	203-714-2		01-2119664781-31	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
107-98-2	1-Methoxy-2-propanol			5-10 %
	203-539-1		01-2119457435-35	
	Flam. Liq. 3, STOT SE 3; H226 H336			
124-38-9	Carbondioxide			5-10%
	204-696-9			
	Compressed gas; H280			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to UK REACH Regulation

Flux-Remover

Revision date: 16.05.2024

Product code: 107

Page 3 of 9

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	918-668-5	Hydrocarbons, C9, aromatics	20-40%
		inhalation: LC50 = 6193 mg/l (vapours); dermal: LD50 = 3160 mg/kg; oral: LD50 = 3492 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up**For containment**

For cleaning up Wash with plenty of water.

Safety Data Sheet

according to UK REACH Regulation

Flux-Remover

Revision date: 16.05.2024

Product code: 107

Page 4 of 9

For cleaning up

For cleaning up Wash with plenty of water.

Other information

Ventilate affected area.

6.4. Reference to other sections

No data available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breathe gas/fumes/vapour/spray.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature 20°C

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
109-87-5	Dimethoxymethane	1000	3160		TWA (8 h)	WEL
		1250	3950		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Safety Data Sheet

according to UK REACH Regulation

Flux-Remover

Revision date: 16.05.2024

Product code: 107

Page 5 of 9



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses.

Hand protection

EN ISO 374 Tested protective gloves are to be worn: NBR (Nitrile rubber) For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. NBR (Nitrile rubber)

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol	
Colour:	colourless	
Odour:	characteristic	
Boiling point or initial boiling point and boiling range:		82,4 °C
Lower explosion limits:		1,2 vol. %
Upper explosion limits:		12 vol. %
Flash point:		<0 °C
Auto-ignition temperature:		270 °C
Vapour pressure:		40 hPa
(at 20 °C)		
Density (at 20 °C):		0,84 g/cm ³

9.2. Other information

Other safety characteristics

Solvent content: 95%

Further Information

Keine weiteren relevanten Informationen verfügbar.
No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

Safety Data Sheet

according to UK REACH Regulation

Flux-Remover

Revision date: 16.05.2024

Product code: 107

Page 6 of 9

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C9, aromatics				
	oral	LD50 3492 mg/kg	Rat	OECD	Prüfrichtlinie 401
	dermal	LD50 3160 mg/kg	Rabbit	OECD	Prüfrichtlinie 402
	inhalation vapour	LC50 6193 mg/l	Rat	OECD	Prüfrichtlinie 403

Irritation and corrosivity

Irritating to eyes. Following inhalation: Lung irritation. Coughing. shortage of breath. After skin contact: irritant.

Sensitising effects

not sensitising.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information

Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

Based on the available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to UK REACH Regulation

Flux-Remover

Revision date: 16.05.2024

Product code: 107

Page 7 of 9

Toxic to aquatic life with long lasting effects.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50	9,2 mg/l	96 h	Fish	
	Acute algae toxicity	ErC50	2,9 mg/l		Alge	
	Acute crustacea toxicity	EC50	3,2 mg/l	48 h	Daphnia pulex (water flea)	

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information
Land transport (ADR/RID)
14.1. UN number or ID number:

UN1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 625

Safety Data Sheet

according to UK REACH Regulation

Flux-Remover

Revision date: 16.05.2024

Product code: 107

Page 8 of 9

Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)
 E0

Inland waterways transport (ADN)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L

Other applicable information (inland waterways transport)
 E0

Marine transport (IMDG)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: See SP277
 EmS: F-D, S-U

Other applicable information (marine transport)
 E0

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
 Hazard label: 2.1



Special Provisions: A145 A167
 Limited quantity Passenger: 30 kg G
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)
 E0
 : Y203

14.5. Environmental hazards

Safety Data Sheet

according to UK REACH Regulation

Flux-Remover

Revision date: 16.05.2024

Product code: 107

Page 9 of 9

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Solvent Naphta Light

14.6. Special precautions for user

Keine weiteren relevanten Informationen verfügbar.
No further relevant information available.

14.7. Maritime transport in bulk according to IMO instruments

Keine weiteren relevanten Informationen verfügbar.
No further relevant information available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 6,45 % (54,18 g/l)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information**Abbreviations and acronyms**

Compressed gas
Flam. Liq: Flammable liquids
Asp. Tox: Aspiration hazard
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Chronic: Chronic aquatic hazard

Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)