

# Desktop Soldering Robot

## QUICK ET9394F/9494F/9594F



### Feature

#### X/Y Rail

Double-rail for X/Y axis, precise moving.

#### Y Motor

Closed loop control, no out-of-step, precise speed control

#### Heating Controller

High frequency current heating, fast heating and thermal recovery, intelligent temperature compensation

#### Alarm Functions

Temperature abnormal and solder wire lack alarm available.

#### Communication Ports

DB37, DB9

#### Protocol

RS485, RS422, RS232

#### Wire Feeding

Wire feeder fixed on the soldering iron, shorten feeding distance.

### Specifications

Model	QUICK ET9394F-A	QUICK ET9494F-A	QUICK ET9594F-A	
Axis	4	4	4	
Power Consumption	600W	600W	600W	
Power of Heating Controller	200W	200W	200W	
Moving Range	X/Y/Z	300/300/100mm	400/400/100mm	500/500/100mm
	R	±180°	±180°	±180°
	X/Y	0.1~800 mm/sec	0.1~800 mm/sec	0.1~800 mm/sec
Speed Range	Z	0.1~300 mm/sec	0.1~300 mm/sec	0.1~300 mm/sec
	R	0-800° /sec	0-800° /sec	0-800° /sec
Repeatability	X/Y/Z	± 0.01 mm	± 0.01 mm	± 0.01 mm
	Z	3kg	3kg	3kg
Machine Load	Platform	8kg	8kg	8kg
		340*400mm		
Effective Range(Soldering Area)	260*300mm	340*400mm	440*500mm	
Overall Dimension(W*D*H)	645x579x899mm	745x679x899mm	845x779x899mm	
Weight	70kg	80kg	100kg	

### Optional Accessories



9036 Tip Calibration Device



9039 N2 Generator



Fume Extractor



371T Series

Wire Feeding & Cutting Device

### Overall Dimension

